

Actor 5-24VDC

The **Kadex**[®] 5-24VDC actuator is a low voltage actuator and has 2 outputs and 2 inputs. The device is mainly used for the following applications:

- Convert dry contacts to wireless
- Control sun protection systems

The Actor 5-24VDC is designed as a static device and should be mounted.

Software updates and upgrades can be installed remotely (FOTA) from the Kadex Pro Server. The Kadex Pro Server automatically checks the product for correct operation such as; operation, battery voltage and signal strength.



VARIATIONS

Actor 5-24Vdc 2 + 2 Channel	210619502
Actor 5-24Vdc Motor Control	210609508

General Information

Housing	ABS
Colour	Grey
Weight	35 gram
Protection class	IP 20
Operation Frequency	868MHz
Power supply	5-24VDC
Supported gateways	Kadex Master Locator
Antenna	Integrated
Installation wire diameter	Max. 1.5 mm ²
Interface	2 x switching input to GND, no load allowed! Program/ reset button
Feedback	Blue LED
Output	2 x; Max. 150mA @ 60Vdc per output
Measurements	71 x 50 x 28 mm
Temperature range	
Operation	-10 °C up to 40 °C
Storage	-20 °C up to 70 °C
Relative air humidity	90% at 25 °C

CE conformity according to directive 2014/53/EU (RED)

Radio	EN 300 220-2 V3.2.1
EMC	EN 301 489-3:V2.1.1
Safety	EN 62368-1:2014 + A11:2017
Health	EN 62479:2010
Environment	RoHS (III) Directive 2015/863/EU

* Valid for item

Scope of delivery:
- Actor 5-24VDC